



**124-6027**

Seite/Page 1 / 2

Bild-Nr Fig Fig Fig Bild nr	ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detalj nr	Stückzahl Qty Qte Ctd Qta Antal		Gegenstand Description Designation Descripcion Designazione Benaeming
05	435 639 40	2	Traverse	Lifting beam
06	435 628 40	4	Steckbolzen	Socket pin
07	001 645 98	4	Sicherungsfeder	Locking spring
08	435 642 40	2	Seilrolle kpl. ø 375 einschl. Bild-Nr. 45 u. 46	Sheave assy. incl. fig-nos: 45 and 46
09	435 636 40	3	Distanzring	Spacer
10	435 637 40	1	Distanzring	Spacer
11	435 634 40	1	Festpunkt	Fixed point
12	435 633 40	2	Achse	Axle
13	393 389 40	2	Achshalter	Axle stirrup
14	307 804 99	4	Schraube	Bolt
15	343 112 99	4	Federring	Lock washer
17	435 632 40	2	Seilschutz	Rope protection
18	307 754 99	8	Schraube	Bolt
19	343 177 99	8	Federring	Lock washer
28	-	1	Abschaltung, kpl. siehe EL-Blatt 132-6285	Cut-off device assy. see page 132-6285
29	268 898 40	1	Schaltgewicht, kpl.	Shift weight assy.
30	394 785 40	1	Drahtseil	Cable
31	001 803 98	1	Drahtseilklemme	Cable clamp
32	308 610 99	1	Schraube	Bolt
33	332 334 99	1	Mutter	Nut
34	435 937 40	1	Rohr ø 15	Pipe
35	002 813 98	1	Steckstift	Guide pin
36	422 115 40	1	Halter (anschweißen)	Retainer (to be welded)
-	418 996 40	1	Elektro-Installation	Electr. installation
45	002 017 98	2	Lager	Bearing
46	505 997 98	4	Sprengring	Snap ring