



124-6111

| Bild-Nr<br>Fig<br>Fig<br>Fig<br>Fig<br>Bild nr | ET-Nr<br>Part-No<br>No. de Piece<br>No. de Pieza<br>No. del Pezzo<br>Detailj nr | Stückzahl<br>Qty<br>Qte<br>Ctd<br>Qta<br>Antal |   | Gegenstand<br>Description<br>Designation<br>Descripcion<br>Designazione<br>Benaemning |
|--|---|--|---|---|
| 00   | 468 836 40  | 1  | Wippstützentraverse, kpl.<br>best. aus Bild-Nr. 01-12 | Derricking bracket lifting beam,<br>assy. consist. of fig-nos: 01-12                  |
| 01   | 468 837 40  | 1  | Wippstützentraverse (SK)                              | Derricking bracket lifting beam   |
| 02   | 394 362 40  | 2  | Seilrolle, kpl.<br>einschl. Bild-Nr. 03 u. 04         | Sheave, assy.<br>incl. fig-nos: 03 and 04   |
| 03   | 002 018 98  | 2  | Lager   | Bearing   |
| 04   | 500 609 98  | 4  | Sprengring  | Snap ring   |
| 05   | 342 158 40  | 1  | Achse   | Axle  |
| 06   | 485 963 40  | 2  | Distanzrohr, L=50,5                                   | Distance sleeve   |
| 07   | 485 964 40  | 4  | Festpunkt   | Fixed point   |
| 10   | 307 804 99  | 4  | Schraube  | Screw   |
| 11   | 343 112 99  | 4  | Federring   | Lock washer   |
| 12   | 317 132 40  | 2  | Achshalter  | Axle stirrup  |
| 15   | -   | 2  | Zwischenseil L=6070<br>siehe EL-Blatt 124-6125b1/07   | Pendant rope<br>see page 124-6125b1/07  |