



124-6185a

Bild-Nr Fig Fig Fig Fig Bild nr	ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detalj nr	Stückzahl Qty Qte Ctd Qta Antal		Gegenstand Description Designation Descripcion Designazione Benaemning
00	778 413 73		Auslegerspitze, kpl.	Boom top section, assy.
01	394 410 40	1	Auslegerspitze (SK)	Boom top section
06	365 293 40	1	Distanzrohr L=212	Distance sleeve
07	407 010 40	1	Seilrolle, kpl. ø 528 einschl. Bild-Nr. 08,09	Sheave, assy. incl. fig-nos: 08,09
08	002 017 98	1	Zylinderrollenlager	Cylindrical roller bearing
09	500 608 98	2	Sprengring	Snap ring
10	365 296 40	1	Distanzrohr L=282	Distance sleeve
11	423 328 40	1	Achse	Axle
12	317 891 40	2	Achshalter	Axle stirrup
13	307 804 99	4	Schraube	Bolt
14	343 112 99	4	Federring	Lock washer
30	423 362 40	1	Distanzrohr L=197	Distance sleeve
31	407 012 40	1	Festpunkt	Fixed point
32	423 360 40	1	Rad	Wheel
33	340 493 99	3	Scheibe	Washer
34	407 010 40	1	Seilrolle, kpl. ø 528 einschl. Bild-Nr. 35,36	Sheave, assy. incl. fig-nos: 35,36
35	002 017 98	1	Zylinderrollenlager	Cylindrical roller bearing
36	500 608 98	2	Sprengring	Snap ring
37	408 894 40	1	Distanzrohr L=202	Distance sleeve
38	423 328 40	1	Achse	Axle
39	317 891 40	1	Achshalter	Axle stirrup
40	307 804 99	4	Schraube	Bolt
41	343 112 99	4	Federring	Lock washer
46	245 120 40	1	Halter	Retainer
47	002 813 40	1	Steckstift	Guide pin
48	-	1	Abschaltung siehe EL-Blatt 132-6285	Cut-off device see page 132-6285
49	394 785 40		Seil 1,5 m	Rope
50	001 803 98	2	Seilklemme	Rope clamp
51	268 898 40	1	Schaltgewicht	Shift weight
52	308 604 99	1	Schraube	Bolt
53	334 682 99	1	Mutter	Nut
54	423 251 40	1	Lasche	Shackle

**Auslegerspitze
Boom top section**

124-6185a

Seite/Page 2 / 2