



179-6039

Bild-Nr Fig Fig Fig Fig Bild nr	ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detailj nr	Stückzahl Qty Qte Ctd Qta Antal		Gegenstand Description Designation Descripcion Designazione Benaemning
01	468 309 40	1	Traverse (ohne Anbauteile)	Lifting beam (w/o mount. parts)
02	459 265 40	11	Seilrolle, kpl. ø 572 einschl. Bild-Nr. 15,16	Sheave assy. incl. fig-nos: 15,16
03	484 125 40	1	Abstandshülse	Sleeve
04	468 337 40	1	Achse	Axle
05	458 492 40	2	Scheibe	Disc
06	307 578 99	8	Schraube	Bolt
07	343 114 99	8	Federring	Lock washer
08	468 336 40	1	Stange	Rod
09	342 081 99	2	Splint	Cotter pin
10	468 335 40	2	Bolzen	Pin
11	001 646 98	2	Sicherungsfeder	Locking spring
12	484 160 40	2	Abstandshülse	Sleeve
13	484 123 40	1	Festpunkt	Fixed point
15	501 452 98	10	Lager	Bearing
16	501 453 98	20	Sprengring	Snap ring
17	-	1	Abschaltung siehe EL-Blatt 124-6285	Cut-off device see page 124-6285
18	484 159 40	1	Rohr	Pipe
19	447 467 40	2	Seitenblech	Side plate
20	484 158 40	1	Rohr	Pipe
21	342 103 99	4	Splint	Cotter pin
22	300 056 99	3	Schäkel	Clevis
23	509 649 40	1	Kette (Länge angeben)	Chain (state length required)
24	307 781 99	3	Schraube	Bolt
25	506 807 98	1	Schäkel	Clevis
26	307 757 99	1	Schraube	Bolt
27	334 627 99	3	Mutter	Nut
28	334 626 99	1	Mutter	Nut
29	334 682 99	1	Skt.-Mutter	Nut
30	287 123 40	1	Skt.-Schraube	Bolt
31	551 162 40	4	Sicherheitsklappstecker	Safety pin
32	580 577 40	1	Adapter	Adapter
33	468 335 40	2	Bolzen	Pin
34	001 646 98	2	Sicherungsfeder	Locking spring