



58-6116

| Bild-Nr Fig Fig Fig Fig Bild nr | ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detailj nr | Stückzahl Qty Qte Ctd Qta Antal | | Gegenstand Description Designation Descripcion Designazione Benaemning |
|--|---|--|-----------------------|---|
| 00 | 583 590 40 | 1 | Zwischenstück 6m kpl. | Extension assy. |
| 01 | 583 575 40 | 1 | Zwischenstück 6m SK | Extension (weldment) |
| 02 | 583 586 40 | 2 | Haltestange 4m | Stay bar |
| 03 | 538 501 40 | 2 | Lasche kpl. | Shackle assy. |
| 04 | 583 588 40 | 2 | Haltestange 1,79m | Stay bar |
| 05 | 507 773 98 | 4 | Steckbolzen | Socket pin |
| 06 | 510 454 98 | 2 | Bolzen | Pin |
| 07 | 538 514 40 | 4 | Bolzen | Pin |
| 08 | 541 868 40 | 4 | Bolzen | Pin |
| 09 | 505 909 98 | 5 | Sicherungsbolzen | Lock pin |
| 10 | 505 908 98 | 2 | Sicherungsbolzen | Lock pin |
| 11 | 007 266 98 | 15 | Sicherungsfeder | Locking spring |
| 12 | 427 684 40 | 4 | Wellenendscheibe | End plate |
| 13 | 307 823 99 | 8 | Schraube | Bolt |
| 14 | 517 206 40 | 1 | Seilabweiser | Rope deflector |
| 15 | 319 157 99 | 3 | Schraube | Bolt |
| 16 | 332 334 99 | 3 | Mutter | Nut |
| 17 | 619 428 40 | 1 | Stabil-Rost | Grid |
| 18 | 508 290 40 | 2 | Halter | Retainer |
| 19 | 307 779 99 | 6 | Schraube | Bolt |
| 20 | 334 678 99 | 6 | Mutter | Nut |
| 21 | 560 881 40 | 2 | Laufrolle | Bottom roller |
| 22 | 560 882 40 | 2 | Rohr | Pipe |
| 23 | 538 699 40 | 2 | Stabil-Rost | Grid |
| 24 | 583 592 40 | 2 | Stabil-Rost | Grid |
| 25 | 307 756 99 | 36 | Schraube | Bolt |
| 26 | 334 690 99 | 36 | Mutter | Nut |
| 27 | 350 763 99 | 72 | Scheibe | Disc |
| 29 | 490 036 40 | 2 | Gummihülse | Grommet |
| 30 | 490 037 40 | 2 | Bügel | Yoke |
| 31 | 506 758 98 | 2 | Flügelmutter | Wing nut |
| 32 | 583 593 40 | 1 | Stabil-Rost | Grid |
| 33 | 619 429 40 | 2 | Blech | Plate |
| 34 | 619 431 40 | 4 | Bolzen | Pin |

**Zwischenstück 6m Typ 2722-30-S
Extension**

58-6116

Seite/Page 2/2