



804-6048

| Bild-Nr Fig Fig Fig Fig Bild nr | ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detailj nr | Stückzahl Qty Qte Ctd Qta Antal | | Gegenstand Description Designation Descripcion Designazione Benaemning |
|--|---|--|---------------------------------------|---|
| 00 | 460 895 40 | 1 | Wipptraverse, kpl. | Fixed bridle assy. |
| 01 | 460 890 40 | 1 | Wipptraverse, SK (ohne Anbauteile) | Fixed bridle (w/o mounting parts) |
| 02 | 467 181 40 | 1 | Balkentraverse | Bar |
| 03 | 467 186 40 | 2 | Kreuzlasche | Cross bracket |
| 04 | 460 460 40 | 9 | Seilrolle | Sheave |
| 05 | 460 890 40 | 1 | Achse | Axle |
| 06 | 460 897 40 | 1 | Bolzen | Pin |
| 07 | 307 830 40 | 2 | Bolzen | Pin |
| 08 | 371 130 40 | 3 | Achshalter | Axle stirrup |
| 09 | 228 447 40 | 2 | Scheibe | Disc |
| 10 | 460 878 40 | 12 | Blech (bei Montage anschweißen) | Plate (to be welded) |
| 11 | 467 064 40 | 4 | Blech (bei Montage anschweißen) | Plate (to be welded) |
| 12 | 444 863 40 | 2 | Distanzring | Spacer |
| 13 | 307 805 99 | 4 | Schraube | Bolt |
| 14 | 307 844 99 | 6 | Schraube | Bolt |
| 16 | 487 296 40 | 2 | Bolzen | Pin |
| 17 | 001 645 98 | 2 | Sicherungsfeder | Locking spring |
| 18 | 492 408 40 | 1 | Walze | Roll |
| 19 | 492 412 40 | 1 | Bolzen | Pin |
| 20 | 319 528 40 | 2 | Achshalter | Axle stirrup |
| 21 | 487 273 40 | 8 | Blech (bei Montage anschweißen) | Plate (to be welded) |
| 22 | 307 802 99 | 4 | Schraube | Bolt |
| 23 | 350 562 99 | 1 | Schmiernippel | Grease nipple |
| 25 | 490 505 40 | 2 | Sicherungsbolzen, kpl. | Lock pin, assy. |
| 26 | 537 689 40 | 2 | Bolzen | Pin |
| 27 | 340 472 99 | 2 | Scheibe | Disc |
| 28 | 342 121 99 | 2 | Splint | Cotter pin |
| 29 | 404 448 40 | 2 | Rohr | Pipe |
| 30 | 537 687 40 | 2 | Blech | Plate |
| 31 | 467 185 40 | 1 | Frierbuchse | Freeze-in bushing |
| 35 | 368 270 99 | 2 | Rillennlager | Bearing |
| 36 | 342 668 99 | 2 | Sicherungsring | Circlip |