



**98-6185**

Seite/Page 1 / 2

Bild-Nr Fig Fig Fig Fig Bild nr	ET-Nr Part-No No. de Piece No. de Pieza No. del Pezzo Detalj nr	Stückzahl Qty Qte Ctd Qta Antal		Gegenstand Description Designation Descrpcion Designazione Benaemning
00	771 617 73		Auslegerspitze, kpl.	Boom top secton, assy.
01	422 935 40	1	Auslegerspitze (SK)	Boom top section
06	364 293 40	1	Distanzrohr L=212	Distance sleeve
07	199 185 40	1	Seilrolle, kpl. ø 528 einschl. Bild-Nr. 08,09	Sheave, assy. incl. fig-nos: 08,09
08	002 017 98	1	Rollenlager	Roller bearing
09	500 608 98	2	Sprengring	Snap ring
10	423 254 40	1	Distanzrohr L=191	Distance sleeve
11	423 328 40	1	Achse	Axle
12	317 891 40	1	Achshalter	Axle stirrup
13	307 804 99	4	Schraube	Bolt
14	343 112 99	4	Federring	Lock washer
15	365 296 40	1	Distanzrohr L=282	Distance sleeve
16	423 327 40	1	Festpunkt	Fixed point
17	423 309 40	1	Rad	Wheel
18	209 025 99	3	Scheibe	Washer
19	267 575 40	1	Seilrolle, kpl. ø 528 einschl. Bild-Nr. 20,21	Sheave, assy. incl. fig-nos: 20,21
20	002 924 98	1	Rollenlager	Roller bearing
21	500 610 98	2	Sprengring	Snap ring
22	423 253 40	1	Distanzrohr L=195	Distance sleeve
23	423 328 40	1	Achse	Axle
24	423 310 40	1	Achshalter	Axle stirrup
27	002 813 40	1	Steckstift	Guide pin
28	-	1	Abschaltung siehe EL-Blatt 132-6285	Cut-off device see page 132-6285
29	394 785 40	1	Seil 1,5 m	Rope
30	001 803 98	1	Seilklemme	Rope clamp
31	268 898 40	1	Schaltgewicht	Shift weight
32	308 604 99	1	Schraube	Bolt
33	334 682 99	1	Mutter	Nut
34	423 251 40	1	Lasche	Shackle
35	001 644 98	1	Sicherungsfeder	Locking spring
36	506 807 98	1	Schäkel	Clevis
37	485 605 40	1	Zugfeder	Draw spring
38	349 554 40	1	Kausche	Thimble
39	307 757 99	1	Schraube	Bolt
40	334 690 99	1	Mutter	Nut
44	435 047 40	2	Seilrolle	Sheave
45	340 470 99	4	Scheibe	Washer
46	342 083 99	2	Splint	Cotter pin
47	394 961 40	1	Kunststoffseil 12m lg.	Reev-in rope

**Auslegerspitze  
Boom Top Section**

**98-6185**

Seite/Page 2 / 2